



Flexstrip 120

Fabric-coated waterproof elastic joint sealing tape

Drykos® **Flexstrip 120** is a waterproof joint cover tape consisting of an elastomeric core with high deformation capacity, fully coated on both sides with absorbent fabric. The presence of the textile coating allows for excellent impregnation and integration with cementitious waterproofing systems, ensuring high adhesion to the substrate and the creation of a continuous and durable system. Thanks to its high elasticity and ease of application, Drykos® **Flexstrip 120** is particularly suitable for sealing and waterproofing joints in surface waterproofing systems.

TECHNICAL PERFORMANCE

Characteristic	Test method	Standard requirements	Performance
Width			120 mm
Thickness			0.7 mm
Lateral elongation at break	EN ISO 527-3		335 %
Longitudinal tensile strength	EN ISO 527-3		104 N / 15 mm
Lateral tensile strength	EN ISO 527-3		23 N / 15 mm
Elongation at break	EN ISO 527-3		70 %
Stress at 25% elongation	EN ISO 527-3		0.31 N/mm
Stress at 50% elongation	EN ISO 527-3		0.34 N/mm
Resistance to hydrostatic pressure	EN 1928 B		> 1.5 bar
UV resistance	EN ISO 4892-3		500 h

NOTES

This "light" version of the technical data sheet provides a selection of the product's main descriptive and performance characteristics. While the data contained herein corresponds to our current scientific and technical knowledge, it is indicative and not exhaustive. For complete specifications, detailed technical information, conditions of use, and official updates, please refer exclusively to the full technical data sheet, available in its latest revision at www.drykos.com.



Full technical datasheet



DRYKOS S.r.l.

Piazza Marconi n. 7 12100 - Tarantasca (CN) - Italia

Tel. + 39 0171 1874992 | E-mail info@drykos.com | Web www.drykos.com

Last update 28/11/2025