


Jointsteel P

Galvanized steel waterstop, coated with adhesive butyl rubber, for waterproof sealing of horizontal construction joints



Drykos® **Jointsteel P** is a metallic waterstop system designed to ensure waterproof sealing of construction joints in water-impermeable reinforced concrete structures.

Drykos® **Jointsteel P** consists of a galvanized steel sheet, coated on both sides with special adhesive butyl rubber, protected by a release film that facilitates installation operations and ensures high adhesion to concrete.

The special flexible coating adheres intimately to the concrete, creating a continuous adhesive-type waterproof barrier that prevents water circulation along the joint.

The system is suitable for reliable sealing of construction joints and controlled cracking joints, both in cast-in-place concrete structures and in combination with precast panel walls, with reference to both horizontal joints between foundation slabs and retaining walls in elevation and vertical joints.

Drykos® **Jointsteel P** is also suitable for applications in the presence of pressurized water, ensuring hydraulic sealing of the joint up to a maximum persistent hydrostatic pressure of 2 bar, equivalent to approximately 20 m of water column.

TECHNICAL PERFORMANCE

Characteristic	Test method	Standard requirements	Performance
Length			20 m
Height			160 mm / 240 mm
Sheet thickness			~ 0.6 mm
Special coating thickness			~ 0.15 mm
Total thickness			~ 0.9 mm

NOTES

This "light" version of the technical data sheet provides a selection of the product's main descriptive and performance characteristics. While the data contained herein corresponds to our current scientific and technical knowledge, it is indicative and not exhaustive. For complete specifications, detailed technical information, conditions of use, and official updates, please refer exclusively to the full technical data sheet, available in its latest revision at www.drykos.com.



Full technical datasheet



DRYKOS S.r.l.

Piazza Marconi n. 7 12100 - Tarantasca (CN) - Italia

Tel. + 39 0171 1874992 | E-mail info@drykos.com | Web www.drykos.com

Last update 28/11/2025